

**TARA**  
SYSTEMS

## APPLICATIONS

Truck scales  
Fertilizer blending tanks  
Batching hoppers  
Feed milling and mixing  
Hopper scales  
All general purpose weighing



Sun Buster

**TARA**

**SYSTEMS**

## MODELS

RM-6 & RM-3

HIGH INTENSITY  
OUTDOOR REMOTE  
DISPLAY 6 " & 3 "  
TALL DIGITS

## FEATURES

RM-3

NEMA 4X non-metallic enclosure for harsh environments.  
Automatic learn for quick setup.

RS232 - 20ma & optional RS485

High brightness LED can be seen in direct sunlight at distances up to 200 feet.

Long life - NO moving parts.  
3 INCH 75 foot visibility.

6 INCH 200 foot visibility

120 volt operation

12 volt DC models available

Low Cost

No Maintenance



RM-6

## APPLICATIONS

The model RM-6 & RM-3 remote display is a versatile outdoor remote display for all types of weighing environments. The Ultra-bright LED display is all solid-state and has no parts to repair or replace. The lights are of the same type that are being used in automotive and traffic signal applications.

The RM-6 has large 6 inch tall digits that can be seen in bright sun at a distances over 200 feet and the RM-3 is visable over 75 feet.

The standard features provide for easy setup. The unit will learn the baud rate and data bits of the sending unit, and configure itself to receive and display the correct weight data.

When data is received, the first group of numbers will be pulled out and displayed. If more than 6 digits are received, the display will show the least significant 6 digits. If a decimal point is detected, it will be displayed in the correct location. If a minus sign is detected, the minus sign will be displayed in front of the least significant 5 digits.

Standard RS232 from 300 to 9600 baud rates, and 20ma current loop (Passive and Active) can be used.

## SPECIFICATIONS

Power .....	120vac +- 10% 120 watts typical 220vac optional - 12 volt DC optional
Enclosure .....	NEMA 4X watertight and corrosion proof polycarbonate RM-6 23 ½ by 12 ½ by 5 ” RM-3 14 ½ by 6 1/2 ½ by 4 ” with screw on mounting ears for wall or pole mounting.
Display .....	High visibility ultra-bright LED - 6 digits
Baud rate.....	300 to 9600 automatic selection.
Data input .....	Standard ASCII characters.
Interface.....	RS232, 20ma current loop (Optional RS422.485)
Operating temperature ....	0-40c
Humidity.....	0 to 80% non-condensing

TARA SYSTEMS

Manufacturers of Electronic Weighing Devices